



ON-TCP Product Data Sheet

Thermally Conductive Paste

DESCRIPTION

ON-TCP is a thermal conductive, heat sink compound which is designed to meet the demanding applications which require excellent heat transfer. ON-TCP offers no separation and excellent dispersion and stability. ON-TCP does not dry out, harden or melt.

TYPICAL PROPERTIES

Operating Temperature	-50° - 200° C
Specific Gravity	2.6g/cc
Thermal Conductivity	.63 W/m-K

WARNING: THIS MATERIAL IS SOLD FOR INDUSTRIAL USE ONLY

Uncured epoxy adhesives - consisting of resin and hardener components - may cause dermatitis, skin sensitization or other allergic responses. Prevent all contact with skin and eyes. If contact occurs, flush immediately with plenty of water (get prompt medical attention for eyes). Keep away from heat and open flames. KEEP OUT OF REACH OF CHILDREN. Immediately clean up any spills that may occur.

ANGSTROM SCIENCES, INC. MAKES NO EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS OR OTHERWISE with respect to its products. In addition, while the information contained herein is believed to be reliable, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. All recommendations or suggestions for use are made without guarantee in as much as conditions of use are beyond our control. The properties given are TYPICAL VALUES and are not intended for use in preparing specifications. Users should make their own tests to determine the suitability of this product for their own purposes.

Updated January 2008