ARSENIC SELENIUM SILICON ALLOY SAFETY DATA SHEET DATE OF LAST REVISION: 01/29/18

Section 1: Identification

Product Name: Arsenic Selenium Silicon Alloy

Company: Angstrom Sciences, Inc. 40 South Linden Street Duquesne, PA 15110 For more information call: 412-469-8466 (Monday - Friday 9:00 AM -5:00 PM EST)

Section 2: HAZARD IDENTIFICATION

Danger



Hazard Statements:

Signal Word:

H228: Flammable solid H301 + H331: Toxic if swallowed or inhaled H373: May cause damage to organs through prolonged or repeated exposure

Precautionary Statements: P210: Keep away from heat/sparks/open flames/hot surfaces - No smoking P240: Ground/bond container and receiving equipment P241: Use explosion-proof electrical/ventilating/lighting/equipment P260: Do not breath dust/fume/gas/mist/vapors/spray P280: Wear protective gloves/protective clothing/eye protection/face protection P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician P304 + P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing P321: Specific treatment (see on this label) P405: Store locked up P501: Dispose of contents/container in accordance with local/regional/national/international regulations

ARSENIC SELENIUM SILICON ALLOY SAFETY DATA SHEET

HMIS Health Ratings (0-4):	
Health:	З
Flammability:	2
Physical:	1

Section 3: Composition/Information on Ingredients

Chemical Family: Additional Names:	Alloy N∕A
Arsenic (As):	
Percentage	0-100 wt%
CAS#:	7440-38-2
EC#:	231-148-6
Selenium (Se):	
Percentage:	0-100 wt%
CAS#:	7782-49-2
EC#:	231-957-4
Silicon (Si):	
Percentage:	0-100 wt%
CAS#:	7440-21-2
EC#:	231-130-8

Section 4: FIRST AID MEASURES

General Treatment: Remove any contaminated clothing. Supply oxygen if breathing is difficult. Seek medical attention if symptoms persist.

Special Treatment: None

Important Symptoms: None

Eye Contact:	Flush eyes with water, blinking often for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
Skin Contact: Inhalation:	Wash affected area with mild soap and water. Remove any contaminated clothing Remove to fresh air. If required, give artificial respiration. Seek medical advice.
Ingestion	Do not induce vomiting. Seek medical attention.

Section 5: FIRE FIGHTING MEASURES

Extinguishing Media:	Do not use water for metal fires - use CO ₂ , sand, extinguishing powder.
Flammability:	Non-Flammable. except as powder
Special Fire Fighting Procedure	: Use full-face, self contained breathing apparatus with full protective
	clothing to prevent contact with skin and eyes. See section 10 for
	decomposition products.

Section 6: ACCIDENTAL RELEASE MEASURES		
Personal Precautions:	Wear appropriate respiratory and protective equipment specified in special	
	protection information. Isolate spill area and provide ventilation. Vacuum up	
	spill using a high efficiency particulate absolute (HEPA) air filter and place in a	
	closed container for disposal. Take care not to raise dust.	
Environmental Precautions:	Isolate runoff to prevent environmental pollution.	

ARSENIC SELENIUM SILICON ALLOY SAFETY DATA SHEET

Section 7: HANDLING AND STORAGE

Handling Precautions for safe handling: Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities Store in a cool dry place in a tightly sealed container. Store apart from materials and conditions listed in Section 10.

Work/Hygienic Maintenance: Do not use tobacco or food in work area. Wash thoroughly before eating and smoking. Do not blow dust off clothing or skin with compressed air.

Ventilation: Provide sufficient ventilation to maintain concentration at or below threshold limit.

Section 8: EXPOSURE CONTROL/PERSONAL PROTECTION

Permissible Exposure Limits: Threshold Limit Value:	O.1 mg/m ³ as As, long-term value O.1 mg/m ³ as As, long-term value
Special Equipment:	None
Respiratory Protection:	Use a respirator with type N95 (USA) or PE (EN 143) cartridges as a backup to engineering controls. Risk assessment should be performed to determine if purifying respirators are appropriate. Only use equipment tested and approved under appropriate government standards.
Protective Gloves:	Nitrile Rubber Gloves
Eye Protection:	Safety glasses or goggles
Body Protection:	Protective work clothing. Wear close-toed shoes and long sleeves/pants.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Form:	Powder, Granules, Pellets, Sputtering target, Custom parts
Color:	Grey/Brown
Odor:	Odorless
Water Solubility:	Insoluble
Boiling Point:	N/A
Melting Point:	N/A
Flash Point:	N/A
Autoignition Temperature:	N/A
Density:	N/A
Molecular Weight:	N/A

Section 10: STABILITY AND REACTIVITY

Reactivity:	Halogens, Interhalogens, Oxidizing agents
Chemical Stability:	Stable under recommended storage conditions
Incompatible Conditions:	Oxidizing agents, Acids
Hazardous Decomposition Products:	Arsenic oxides, Selenium oxides, Silicon oxides

Section 11: TOXICOLOGICAL INFORMATION

Potential Health Effects: Eyes: May cause irritation

ARSENIC SELENIUM SILICON ALLOY SAFETY DATA SHEET

Skin: Ingestion: Inhalation: Chronic: Signs & Symptoms: Aggravated Medical Conditions: Median Lethal Dose: Carcinogen:	May cause irritation Toxic Toxic N/A N/A N/A 3160 mg/kg for rat by mouth (as Si) Arsenic: EPA-A: human carcinogen: sufficient evidence from epidemiologic studies to support a casual association between exposure and cancer. IARC-1: Carcinogenic to humans: sufficient evidence of carcinogenicity ACGIH A1: Confirmed human carcinogen: Agent is carcinogenic to humans based on epidemiologic studies of, or convincing clinical evidence in, exposed humans. Carcinogen as defined by OSHA NTP-K: Known to be carcinogenic: sufficient evidence from
Additional information:	NTP-K: Known to be carcinogenic: sufficient evidence from human studies To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.

Section 12: ECOLOGICAL INFORMATION


Aquatic Toxicity:	Low
Persistence Bioaccumulation Toxicity:	No
Very Persistent, Very Bioaccumulative:	No
Notes:	N/A

Section 13: DISPOSAL CONSIDERATIONS

Dispose of in accordance with local, state, national, and international regulations

Section 14: TRANSPORT INFORMATION

Hazardous: Hazardous for transportation



ARSENIC SELENIUM SILICON ALLOY SAFETY DATA SHEET

UN Number: UN1558 **Proper Shipping Name:** Arsenic compounds, solid, n.o.s. inorganic (Arsenic Selenium Silicon)

Section 15: REGULATORY INFORMATION

Sec 302 Extremely Hazardous:	No
Sec 304 Reportable Quantities:	N/A
Sec 313 Toxic Chemicals:	Yes

Section 16: OTHER INFORMATION

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfill his obligations regarding the use of hazardous products.