MANGANESE

SAFETY DATA SHEET

DATE OF LAST REVISION: 04/30/15

Section 1: Identification

Product Name: Manganese

CAS Number: 7439-93-2 / **EC Number:** 231-102-5

Company: Angstrom Sciences, Inc.

40 South Linden Street
Duquesne, PA 15110
For more information call: 412-469-8466

(Monday - Friday 9:00 AM -5:00 PM EST)

Section 2: HAZARD IDENTIFICATION

Signal Word: Warning



Hazard Statements: H228: Flammable solid (powder)

Precautionary Statements: P210: Keep away from heat/sparks/flame. No smoking.

P240: Ground/bond container and receiving equipment.

HMIS Health Ratings (0-4): Powder Pieces & Larger

Health: 1 O
Flammability: 2 O
Physical: 1 O

Section 3: Composition/Information on Ingredients

Chemical characterization: Metal

Additional Names: None

MANGANESE SAFETY DATA SHEET

CAS# Description: 7439-96-5

Percentage: 100 wt% **EC number:** 231-105-1

Section 4: FIRST AID MEASURES

General Treatment: Seek medical attention if symptoms persist.

Special Treatment: None Important Symptoms: None

Eye Contact: Flush eyes with water, blinking often for several minutes. Remove contact lenses if

present and easy to do. Continue rinsing.

Skin Contact: Wash affected area with mild soap and water. Remove any contaminated clothing.

Inhalation: Remove to fresh air. If required, give artificial respiration. Seek medical advice.

Ingestion: Give one to two glasses of water and induce vomiting. Never induce vomiting or give

anything by mouth to an unconscious person.

Section 5: FIRE FIGHTING MEASURES

Suitable extinguishing Media: Do not use water for metal fires - use CO₂, sand, extinguishing powder **Flammability:** Non-Flammable

Special Fire Fighting Procedure: Use full-face, self contained breathing apparatus with full protective clothing to prevent contact with skin and eyes. See section 10 for decomposition products.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear appropriate respiratory and protective equipment specified in special protection information. Isolate spill area and provide ventilation. Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for disposal. Take care not to raise dust.

Environmental Precautions: Isolate runoff to prevent environmental pollution.

Section 7: HANDLING AND STORAGE

Handling Precautions for safe handling: Wash thoroughly after handling

Conditions for safe storage, including any incompatibilities Store in a cool dry place in a tightly sealed container. Store apart from materials and conditions listed in Section 10.

Work/Hygienic Maintenance: Do not use tobacco or food in work area. Wash thoroughly before eating and smoking. Do not blow dust off clothing or skin with compressed air.

Ventilation: Provide sufficient ventilation to maintain concentration at or below threshold limit.

Section 8: EXPOSURE CONTROL/PERSONAL PROTECTION

Permissible Exposure Limits: 5 mg/m³ as Mn, ceiling limit value

MANGANESE

SAFETY DATA SHEET

Threshold Limit Value: 0.02 mg/m³ as Mn, respirable, long-term value

0.1 mg/m³ as Mn, inhalable fraction, long-term value

Special Equipment: None

Respiratory Protection: Dust respirator

Protective Gloves: Rubber Gloves

Eye Protection: Safety glasses or goggles, Full face protection

Body Protection: Protective work clothing. Wear close-toed shoes and long sleeves/pants.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Form: Granules, Powder, Pellets, Sputtering target, Custom parts

Color:Metallic GreyOdor:OdorlessWater Solubility:Insoluble, rustsBoiling Point:2095°CMelting Point:1246°C

Flash Point: N/A
Autoignition Temperature: N/A
Density: 7.21 g/cc
Molecular Weight: 54.938 g/mol

Section 10: STABILITY AND REACTIVITY

Reactivity: Reacts with oxidizing agents

Chemical Stability: Stable under recommended storage conditions

Incompatible Conditions: None

Hazardous Decomposition Products: Metal oxide fume

Section 11: TOXICOLOGICAL INFORMATION

Potential Health Effects:
Eyes: May cause irritation
Skin: May cause irritation
Ingestion: May cause irritation
Inhalation: May cause irritation

Chronic: Chronic exposure to manganese may cause impairment to the central nervous system. Symptoms include sluggishness, sleepiness, muscle weakness, and loss of facial muscle control, edema, emotional disturbances, spastic gait and falling. Chronic manganese poisoning may develop after as little as three months of heavy exposure but usually cases develop after one to three years of exposure.

Signs & Symptoms: N/A

MANGANESE SAFETY DATA SHEET

Section 12: ECOLOGICAL INFORMATION

Aquatic Toxicity: Low

Persistence Bioaccumulation Toxicity: No Very Persistent, Very Bioaccumulative: No

Notes: N/A

Section 13: DISPOSAL CONSIDERATIONS

Dispose of in accordance with local, state, national, and international regulations

Section 14: TRANSPORT INFORMATION

Hazardous: Hazardous as powder only



Hazard Class: 4.1 Flammable solids

Packing Group: UN3089

UN Number:

Proper Shipping Name: Metal powders, flammable, n.o.s. (Manganese)

MANGANESE SAFETY DATA SHEET

Section 15: REGULATORY INFORMATION

Sec 302 Extremely Hazardous: No

Sec 304 Reportable Quantities: N/A

Sec 313 Toxic Chemicals: No

Section 16: OTHER INFORMATION

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfill his obligations regarding the use of hazardous products.