

# ONYX® 3" DC / IC Target | MAG.II

## Metric Specifications

~	~ "		<b>+-</b>	110	4i,	
	υı	15	u	uc	uc	ж

Anode	304 Stainless Steel
Cathode Body	OFHC Copper
Insulator	CTFE

## **Cooling Requirements**

Flow Rate at Maximum Power	0.07 LPS
Maximum Input Pressure, Open Drain	4 BAR
Maximum Input Temperature	20 °C

#### Dimensions

Α	117.9 mm	⊬————————————————————————————————————
В	119.2 mm	
С	25.4 mm	
		±

#### General

Magnetic Enhancement	Permanent (NdFeB) Encapsulated
Maximum Temperature	100 °C
Source to Substrate Distance	50.8 mm - 304.8 mm
Weight, Approximate Without Options	4.6 kg

### Maximum Sputtering Power \*

Cathode Voltage	100 - 1500 Volts
Direct Cooled Mode, DC	2 kW
Direct Cooled Mode, RF	1 kW
Discharge Current	0.1 - 4 Amps
Indirect Cooled Mode, DC	1.5 kW
Indirect Cooled Mode, RF	700 Watts
Operating Pressure	0.5 - 50 mTorr

#### Mounting, Standard

Power Cable, DC	RG393
Power Cable, RF	1675A
Power Connector, DC	Type N Connector, External Threads
Power Connector, RF	Type HN Connector, External Threads
Stem, Outer Dimension Tubing	25.4 mm
Water, Outer Dimension Tubing	9.6 mm

#### Target

Cooling	Direct / Indirect
Diameter	76.2 mm / 105.0 mm
Form	Circular / Planar
Thickness, Magnetic	3.2 mm Ni
Thickness, Non-Magnetic	6.4 mm / 11.4 mm

#### Specifications Disclaimer

- All Angstrom Sciences NdFeB magnets are totally encapsulated and protected from degradation by water.
- · All sources are available in external configurations.
- Magnetic material calculations are optimized with Nickel targets.
- \* Maximum power for cathode only, a target material's properties, such as, thermal and electrical conductivity may limit the maximum process power level.
- Some custom-engineered and specialty magnetrons may not meet standard specifications.
- Specifications are subject to change without notice.
- Thickness will vary depending upon coercivity of target material.
- Typical performance. Results may vary with process parameters such as pressure, flow rate, target material, and substrate rotation, etc.

Please contact us for specifications regarding your application.

Angstrom Sciences | Call +1-412-469-8466 | www.angstromsciences.com